

PCD - 8

Conference System

Get Instant Feedback From Your Audience



PCD - 8 Conference System

CSP - P8 Power Unit

Open mode with auto switch-off: To select the maximum number of delegate microphones to be activated simultaneously (1, 2, 3 or 4). The microphone switches off automatically if the speaker stops speaking for 30 seconds. The microphone can manually be switched off by pushing the button on the delegate unit.

Open mode: To select the maximum number of delegate microphone to be activated simultaneously (1, 2, 3 or 4). The microphone must be switched on or off manually by pushing the button on the delegate unit.

Override mode: Only one delegate microphone can be activated. If a new delegate presses his microphone button, the microphone unit of the current speaker will be switched off.

Chairman only mode: Only the chairman units can be activated.

Test mode: For proper installation check. All the lighting and LED's of the connected units will lit, if properly connected.

CSC - C8 Chairman Unit

Chairman unit with built-in loudspeaker, two 3.5mm stereo headphone sockets and red (LED) indicator on the unit base and microphone head. When the microphone is on, the red indicators will on.

Loudspeaker Built-in will be muted automatically when the microphone is on in order to avoid the feedback. The chairman unit has the priority function to over rule / mute all active microphones of delegate units in the system and keeps the chairman unit on for as long as the button is pressed.

The chairman unit has the same function as the delegate unit with the exception of a priority button.

Mains voltage is 100 - 240Vac. + - 10%, 50/60HZ.

7-pole circular female socket for loop through connection to the next unit. 2M flying lead connection cable with sturdy moulded 7-pole circular male connector for connection to the previous unit or CSP - P8 Power Unit. The cable is shielding conductor in order to avoid the interference of the electromagnetic wave.

The chairman unit isn't be restricted by the controller, and can be in series at any position of the system. If the systems with several chairman units, these chairman units are independently, they can't be controlled by the controller. Hand in hand connection. Weight : 0.88kg (1.936 pounds).

Dimension (height x width x thickness) 63 x 124 x 172 mm (2.5 x 4.9 x 8 inches), not including microphone.

CSD - D8 Delegate Unit

Delegate unit with loudspeaker built-in, two 3.5mm stereo headphone sockets and red (LED) indicator on the unit base and microphone head. When the microphone is on. the red indicators will on.

Built-in loudspeaker will be automatically muted when the microphone is on, in order to avoid the feedback.

Mains voltage is 100 - 240Vac. + - 10%, 50/60HZ.

7-pole circular female socket for loop through connection to the next unit. 2M flying lead connection cable with sturdy moulded 7-pole circular male connector for connection to the previous unit or CSP - P8 Power Unit. The cable is shielding conductor in order to avoid the interference of the electromagnetic wave.

Hand in hand connection. Weight : 0.8 kg (1.76 pounds).

Dimension (height x width x thickness) 63 x 124 x 172 mm (2.5 x 4.9 x 6.8 inches), not including microphone.

Authorized by :